

# CURRENT TRANSFORMERS

## METERING CLASS CURRENT TRANSFORMER MODEL JAB-0C

### FEATURES

- Revenue Metering Applications
- Indoor Rated
- Window I.D. - 4.50" x 3.50"
- Shorting Link Provided
- Designed for installation over the secondary bushings of pad mounted transformers.
- An 85°C version is available. Contact Flex-Core for catalog numbers.

### 600V CLASS

MADE IN U.S.A.



### SPECIFICATIONS

Frequency ..... 50-60Hz  
 Insulation class ..... 0.6kV, 10kV BIL Full Wave  
 Terminals ..... Tin plated brass, compression type with 0.275" diameter crosshole for 1/4-28 clamp screw.  
 Weight ..... Approximately 8.25 Lbs.

Manufactured to meet the requirements of ANSI/IEEE C57.13

APPLICATION AND ORDERING DATA								
CATALOG NUMBER	CURRENT RATIO	ANSI METERING CLASS AT 60 Hz					CONTINUOUS THERMAL RATING FACTOR	
		B0.1	B0.2	B0.5	B0.9	B1.8	@30°C	@55°C
750X136202	200:5	0.3	-	-	-	-	4.0	2.9
**750X136668	200:5	0.3	0.3	-	-	-	4.0	4.0
**750X136660	300:5	0.3	0.3	0.3	-	-	3.0	2.2
750X136203	300:5	0.3	0.3	-	-	-	4.0	2.9
750X136204	400:5	0.3	0.3	-	-	-	4.0	2.9
**750X136667	400:5	0.3	0.3	0.3	-	-	4.0	2.9
750X136205	500:5	0.3	0.3	0.3	-	-	3.0	2.2
750X136206	600:5	0.3	0.3	0.3	-	-	3.0	2.2
750X136208	800:5	0.3	0.3	0.3	-	-	3.0	2.2
750X136210	1000:5	0.3	0.3	0.3	-	-	2.0	1.5
750X136212	1200:5	0.3	0.3	0.3	-	-	2.0	1.5
750X136215	1500:5	0.3	0.3	0.3	0.3	-	2.0	1.5
**750X136465	1500:5	0.3	0.3	0.3	0.3	-	3.0	2.4
750X136220	2000:5	0.3	0.3	0.3	0.3	0.3	1.5	1.1
750X136230	3000:5	0.3	0.3	0.3	0.3	0.3	1.33	1.0
750X136655	4000:5	0.3	0.3	0.3	0.3	0.3	1.0	0.7

\*\* Cast Resin  
 Height - 2.5"  
 Weight - 11.7Lbs.

**FLEX-CORE®**  
 Div. Morlan & Associates, Inc.  
 4970 Scioto Darby Rd. Hilliard, Ohio 43026

WWW.FLEX-CORE.COM  
 sales@flex-core.com

PHONE (614) 889-6152  
 TECH. ASSISTANCE (614) 876-8308  
 FAX # (614) 876-8538