

FREQUENCY TRANSDUCERS

FREQUENCY TRANSDUCER

MODEL AFT

FOR USE ON POWER FREQUENCY APPLICATIONS

FEATURES

- High accuracy over wide frequency ranges.
- Provides analog output which is proportional to the instantaneous frequency of the input signal.
- UL and CUL listed.

APPLICATIONS

- For use on any application that requires indication or recording of instantaneous frequency variations.
- Each model covers all input voltages from 3V to 575V.

INPUT FREQUENCY Hz	STANDARD OUTPUTS MODEL AFT-					
	0-1mA _{dc}	0-10V _{dc}	0-5V _{dc}	4-20mA _{dc}	4-20mA _{dc} *	0-20mA _{dc}
45-55	050-10B	050-10D	050-10X5	050-10E	050-10E2	050-10EA
55-65	060-10B	060-10D	060-10X5	060-10E	060-10E2	060-10EA
375-425	400-50B	400-50D	400-50X5	400-50E	400-50E2	400-50EA
0-10	010B	010D	010X5	010E	010E2	010EA
0-55	055B	055D	055X5	055E	055E2	055EA
0-65	065B	065D	065X5	065E	065E2	065EA
0-100	100B	100D	100X5	100E	100E2	100EA
0-425	425B	425D	425X5	425E	425E2	425EA
0-1000	1000B	1000D	1000X5	1000E	1000E2	1000EA



115Vac, 50/60Hz instrument power is required on all units.

Optional 230Vac Instrument Power - Add suffix "-22"

* Output is loop-powered from 15-24V_{dc}
(also requires instrument power)

Consult factory for special frequency ranges.

ORDERING INFORMATION

Example: 55-65 Hz. Input, with
0-5V_{dc} Output
AFT-060-10X5

SPECIFICATIONS

INPUT


Frequency Range See Table
Voltage Range 3-575V
Burden 1.25VA
Overload 575V
Dielectric Test
Input to Output/Inst. Pwr 3250Vac
Inst. Pwr. to Output 2200Vac
Case to Input/Output/Inst. Pwr 2200Vac
Instrument Power 115Vac, 50/60Hz, $\pm 15\%$, 15VA max.
"-22" Option 230Vac, 50/60Hz, $\pm 15\%$, 15VA max.

OUTPUT


ACCURACY $\pm 0.05\%$ Rdg..... $\pm 0.05\%$ Span
Output Loading (Ohms)
0-1mA 0-10K
10V & 5V 2K min.
4-20mA, 0-20mA 0-500
Output Ripple $\pm 1.0\%$ F.S.
Response Time <200ms
Temperature Range -20°C to +60°C
Temperature Effect $\pm 0.005\%/^{\circ}\text{C}$

CONNECTION DIAGRAMS


MODELS WITH B, D, X5, E, EA OPTIONS



MODELS WITH E2 OPTIONS



CASE DIMENSIONS



All Dimensions In Inches

FLEX-CORE®

Div. Morlan & Associates, Inc.

4970 Scioto Darby Rd. Hilliard, Ohio 43026

WWW.FLEX-CORE.COM

sales@flex-core.com

PHONE (614) 889-6152

TECH. ASSISTANCE (614) 876-8308

FAX # (614) 876-8538