

DIGITAL PANEL METERS

UNIVERSAL DIGITAL METER

MODEL FC40

Digital Meter for Monitoring and Measuring



FEATURES

- User selectable inputs
- Universal power supply
- 1/8 DIN standard panel cutout
- 4 red LED digits (0.56")
- Optional IP65 Front Protection


SPECIFICATIONS

0-5Aac Input	10mA resolution
	20mΩ input resistance
	7Aac max input (7 seconds)
	<0.5% F.S. accuracy
0-600Vac Input	1 Volt resolution
	12MΩ input resistance
	600V max input
	<0.3% F.S. accuracy
4-20mA Input	-1999 to 9999 scaling
	4.7Ω input resistance
	25mA max input
	<0.15% F.S. accuracy


GENERAL SPECIFICATIONS

- Response Time300ms
 - Excitation Power (4-20mA)..... 15Vdc @ 30mA
 - Power Requirement..... 18-265Vac or dc
 - Power Consumption0.3 Watts
 - Mechanical.....96x48mm bezel dim.
 -
 - 92x44mm panel cutout
 - 91mm depth behind panel
 - 163 grams (5.7oz)
 - Operating Temp..... 0-50°C (32-122°F)
 - Storage Temp -20 to 70°C (-4 to 150°F)
 - Front Panel Protection..... IP 50
 - Brightness5 levels
 - Factory Setting 0-400Vac
- *Relay and analog signal output modules are available.

CONNECTOR PINOUTS



DIMENSIONS



All Dimensions In Millimeters

FLEX-CORE®

Div. Morlan & Associates, Inc.

4970 Scioto Darby Rd. Hilliard, Ohio 43026

WWW.FLEX-CORE.COM

sales@flex-core.com

PHONE (614) 889-6152

TECH. ASSISTANCE (614) 876-8308

FAX # (614) 876-8538